

VELUM P 5W-30

Description: A synthetic, fuel economy motor oil, developed according the most recent technology, based on specially selected synthetic base oils to which advanced additives are added to obtain the following properties:

- a lower fuel consumption
- suitable for modern catalysts
- a fast cold start
- a safe lubrication film at high temperatures
- extended oil drain intervals
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

Application: This synthetic, fuel economy, "mid SAPS" motor oil is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with extended oil drain intervals. Due to its low SAPS content this product can be applied in vehicles with modern three way catalysts and diesel particle filters.

PREMIUM MOTOR OIL

Specifications:

ACEA C2, C3
API SP
PSA B71 2290
Meets the requirements of:
MB 229.31 / 229.51 / 229.52 / 226.52
Renault RN17 / RN0700 / RN0710

Typicals:

Density at 15 °C, kg/l 0,854

Viscosity -30 °C, mPa.s 6150

Viscosity 40 °C, mm²/s 73,00

Viscosity 100 °C, mm²/s 12,30

Viscosity Index 167

Flash Point COC, °C 240

Pour Point, °C -39

Total Base Number, mgKOH/g 8,2

Sulphate Ash, % 0,64

STALHART

PREMIUM MOTOR OIL