



STALHART

INNOVATION IN ACTION

VELUM MULTI ATF

Description: A synthetic automatic transmission fluid, based on synthetic base oils, formulated with special friction modifiers to obtain the following properties:

- a very high and stable viscosity index
- a very low pour point
- an excellent stability against oxidation
- a positive activity against wear, corrosion and foam
- specific friction properties and consequently low noise and smooth switching
- compatible with synthetic seals
- a quick oil provision at cold start conditions
- red coloured

Application: This fluid may be used for automatic transmissions, which are applied in several North American, European and Asian cars with mentioned specifications. This multi-purpose ATF meets the hardware protection of specified low viscosity specifications, but does not provide maximum fuel economy. Not suitable for Ford Type F, DCT or CVT applications.

Specifications:

Performance level:

Aisin Warner JWS 3309 / 3324 / AW-1

Allison C4 / TES-389 / TES-295, JASO 1-A

BMW 7045E / 8072B / LA2634 / LT71141

DTFR 13C100/110/120/140 / 13C160 / 13C170 / 38B100

Ford Mercon V / XL-12, GM Dexron IID / IIIG / IIIH

Honda DW-1/ATF-Z1, Hyundai/Kia JWS 3314 / NWS 9638

Hyundai/Kia SP-II/SP-III/SP-IV/SP-IV M/SP-IV RR



STALHART

INNOVATION IN ACTION

MAN 339 Type L1/V2/Z2/Z11, Mazda ATF M-III/M-V
MB 236.1/.2/236.3/236.5/236.6/236.7/236.9/236.10
MB 236.11/236.12/236.14/236.15/236.81/236.93
Mitsubishi SP-II/SP-III/SP-IV/J2/J3
Nissan Matic D/J/K/S/W
Subaru ATF / HP, Suzuki 3314 / 3317
Toyota T/T-II/T-III/T-IV, Voith 55.6336
Volvo 97940 / 97341 (AT101)
VW G 052 162 / 052 990 / 055 005 / 055 025
VW G 055 162 / 055 540
ZF TE-ML 04D/05L/09/11A/11B/14B/16L/20B

Typicals

Density at 15 °C, kg/l	0,850
Viscosity 40 °C, mm ² /s	37,60
Viscosity 100 °C, mm ² /s	7,60
Viscosity Index	176
Flash Point COC, °C	220
Pour Point, °C	-45

STALHART[®]

PREMIUM MOTOR OIL