

VELUM 0W30

Description:A synthetic, fuel economy, universal motor oil, developed according the most recent technology, based on specially selected synthetic base oils to which advanced additives are added to obtain the following properties:

- a lower fuel consumption
- suitable for modern catalysts
- a very fast cold start
- a safe lubrication film at high temperatures
- extended oil drain intervals
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

Application: This universal, synthetic, fuel economy, "mid SAPS" motor oil is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with extended oil drain intervals. Due to its low SAPS content this product can be applied in vehicles with modern three way catalysts and diesel particle filters.

Specifications:

ACEA C2
API SP
PSA B71 2312
Meets the requirements of:
PSA B71 2302
Fiat 9.55535-GS1 / DS1

Typicals:

Density at 15 °C, kg/l 0,849

Viscosity -35 °C, mPa.s 6030

Viscosity 40 °C, mm²/s 51,80

Viscosity 100 °C, mm²/s 9,90

Viscosity Index 180

Flash Point COC, °C220

Pour Point, °C -48

Total Base Number, mgKOH/g 11,2

Sulphate Ash, % 0,75

STALHART

PREMIUM MOTOR OIL