



STALHART

INNOVATION IN ACTION

VELUM ATF VI

Description: A very high graded automatic transmission fluid based on special selected synthetic base oils, with a high viscosity index and a number of selected additives to obtain the following properties:

- a very strong dispersion, therefore sludge is restricted to a minimum
- a very low pour point
- very good stability against oxidation and thermal properties
- a positive activity against wear, corrosion and foam
- specific friction properties
- a perfect compatibility with seals and non-ferro metals
- red coloured.

Application: This fluid may be used for automatic gear boxes (including hybrid), electric vehicle (EV) powertrains, power steering units, torque converters and other equipment, for which an ATF is required, which exceeds ATF Dexron III and II. Its special composition causes a longer lifetime of this liquid compared with older Dexron types. This multi-vehicle ATF meets the hardware protection of the specified low viscosity fluids, like AW-2. This product cannot be used in DCT's and CVT's or when an oil with the Ford Type F/G specification is recommended.

Specifications:

Performance level:

Aisin Warner JWS 3309(T-IV)/3324(WS)/AW-1/AW-2

Allison C3/C4 / TES-389/468

BMW ATF 2/3+/6/7 / 7045E/8072B/LA2634/LT71141

Cat TO-2, Chrysler ATF+ / +2 / +3

DTFR 13C100/120/140/150/170/38B100

Ford Mercon/LV/M2C138-CJ/166-H/922-A1/924-A/938-A

Fiat 9.55550-AV5/AV6

GM Dexron VI/II/IID/IIIE/IIIG/IIIH / TASA

Honda ATF 3.0/3.1/DW-1/Z1(except in CVT)

Hyundai/Kia SP-IV RR/M / JWS 3314/9638

Mazda M-III/A7

MB 236.1/2/3/236.5/236.7/236.8/236.9/236.41

Mitsubishi SP-II/SP-III/SP-IV/J2/J3/PA/MA1



STALHART

INNOVATION IN ACTION

Nissan Matic C/D/J/K/P/S/W

Porsche 3403-M115/T-IV, PSA B71 2340

Subaru ATF 5AT/HP, Suzuki ATF 3314/3317

Toyota D-II/D-III/T-III/T-IV/WS

Tesla Model S/3/X

Voith 55.6335.xx (G607), Volvo 97335/97340/1161540

VW G 052 025 / 052 055 / 052 162 / 052 990

VW G 053 001 / 053 025 / 055 005 / 055 025

VW G 055 162 / 055 540 / 060 162

ZF 3-/4-/6-/8-/9-speed / TE-ML 05L/09/11A/B/21L

Typicals:

Density at 15 °C, kg/l 0,845

Viscosity 40 °C, mm²/s 29,60

Viscosity 100 °C, mm²/s 5,90

Viscosity Index 149

Flash Point COC, °C 212

Pour Point, °C -48

STALHART[™]
PREMIUM MOTOR OIL