

## **VELUM R 5W30**

**Description:** A fuel economy, synthetic motor oil, developed according the most recent technology, based on specially selected synthetic base oils. By applying advanced additives the exceptional performance of this low SAPS motor oil is accentuated.

- a lower fuel consumption
- suitable for modern catalysts
- low combustion ash building (low SAPS)
- a fast cold start
- a safe lubrication film at high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

Application: A fuel economy, specially composed synthetic motor oil, recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans. Due to its special composition this product can be applied in vehicles for which the Renault specification RN0720 is asked and are equipped with modern three way catalysts and diesel particle filters. Due to its low SAPS content this motor oil contributes to the extension of the lifetime of particle filters for diesel engines.

Warning: These oils have the lowest SAPS limits and may be unsuitable for use in some engines.

## **Specifications**

ACEA C3, C4
MB-Approval 229.51
Meets the requirements of:



MB 226.51 Renault RN0720

## **Typicals**

Density at 15 °C, kg/l 0,854

Viscosity -30 °C, mPa.s 6320

Viscosity 40 °C, mm<sup>2</sup>/s 72,80

Viscosity 100 °C, mm<sup>2</sup>/s 12,20

Viscosity Index 170

Flash Point COC, °C 216

Pour Point, °C -39

Total Base Number,

mgKOH/g 6,6

Sulphate Ash, % P 0,49 W M O T O R O I L