

## **VELUM W 5W30**

**Description:** A fuel economy, synthetic, universal motor oil, developed according the most recent technology, based on specially selected synthetic base oils and a well balanced choice of advanced additives to obtain the following properties:

- a lower fuel consumption
- mid SAPS content
- suitable for modern catalysts
- a fast cold start
- a safe lubrication film at high temperatures
- extended oil drain intervals
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming.

**Application:** This universal, fuel economy, specially composed motor oil, is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with extended oil drain intervals. This motor oil also contributes to the extension of the lifetime of particle filters. Due to its special composition it is possible to apply this product for the VW 504.00/507.00 requirements, in practice also called VW Longlife III.

For your information: this is the same oil previously sold under the name Tor Extendo NF 5W30. Due to approval related matters, the name has been changed.

## **Specifications**

ACEA C3
API SP
Approved under VW 504.00 / 507.00

MB-Approval 229.51 / 229.52

BMW Longlife-04

Porsche C30

Meets the requirements of:

MB 229.31

Opel OV 040 1547 - D30 / G30

## **Typicals**

Density at 15 °C, kg/l 0,855

Viscosity -30 °C, mPa.s 5980

Viscosity 40 °C, mm<sup>2</sup>/s 69,80

Viscosity 100 °C, mm<sup>2</sup>/s 12,30

Viscosity Index 176

Flash Point COC, °C 224

Pour Point, °C -42

Total Base Number,

mgKOH/g 8,3

Sulphate Ash, % 0,75