



# STALHART

INNOVATION IN ACTION

## VELUM 5W40

**Description:** A universal synthetic motor oil, developed according to the most recent technology and based on specially selected synthetic base oils with a high natural viscosity index. With the addition of a well-balanced choice of advanced additives the following properties are obtained:

- a high and very stable viscosity index
- a high resistance against shearing
- a fast cold start
- a safe lubrication film at very high temperatures
- reduced formation of combustion ashes
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

**Application:** This universal synthetic motor oil is suitable for use in petrol and diesel engines, with or without turbo-charging. Moreover this lubricant is also very suitable for passenger car diesel engines with pump-injector-unit. This product meets the requirements of several OEM's and thus has a wide application.

### Specifications:

ACEA C3

API SN, API SN Plus

BMW Longlife-04

MB-Approval 229.51

Meets the requirements of:

MB 229.31 / 229.52

VW 505.00 / 505.01

Ford M2C917-A



# STALHART

INNOVATION IN ACTION

## Typicals:

Density at 15 °C, kg/l	0,853
Viscosity -30 °C, mPa.s	6080
Viscosity 40 °C, mm <sup>2</sup> /s	75,80
Viscosity 100 °C, mm <sup>2</sup> /s	13,20
Viscosity Index	180
Flash Point COC, °C	220
Pour Point, °C	-36
Total Base Number, mgKOH/g	7,0
Sulphate Ash, %	0,75



STALHART™

PREMIUM MOTOR OIL