

VELUM G 5W30

Description: A universal, synthetic fuel economy motor oil developed according the most recent technology and based on specially selected synthetic base oils with a high natural viscosity index. With the addition of a well-balanced choice of advanced additives the following properties are obtained:

- a lower fuel consumption
- a high and very stable viscosity index
- a high resistance against shearing
- a fast cold start
- a safe lubrication film at very high temperatures
- reduced formation of combustion ashes
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

Application: This universal, fuel saving synthetic motor oil is suitable for use in petrol and diesel engines, with or without turbo-charging. Moreover this lubricant is also very suitable for passenger car diesel engines with pump-injector-unit. This product meets the requirements of several OEM's and thus has a wide application.

Specifications:

ACEA C3
API SN, API SN Plus
MB-Approval 229.31 / 229.51 / 229.52
BMW Longlife-04
Meets the requirements of:
GM dexos 2
Opel OV 040 1547 - D30 / G30
VW 505.00 / 505.01



Typicals

Density at 15 °C, kg/l 0,852
Viscosity -30 °C, mPa.s 5880
Viscosity 40 °C, mm²/s 68,60
Viscosity 100 °C, mm²/s 12,30
Viscosity Index 175
Flash Point COC, °C 228
Pour Point, °C -36

Total Base Number,

mgKOH/g 7,3 Sulphate Ash, % 0,75

STALHART

PREMIUM MOTOR OIL